

SN: 09/535,457

29462

CLEAN VERSION OF EACH REPLACEMENT SECTION/CLAIMSIn the Claims

Kindly amend Claim 1 as indicated following.

Kindly amend Claim 1 as indicated following.

1. A bundle of framing lumber product, comprising:

- (a) a plurality of elongate pieces of lumber operative to assist in layout and assembly of a wall, wherein such wall comprises a bottom plate and a top plate, and a plurality of dimension studs extending between the bottom plate and the top plate at one or more of a limited number of pre-determined stud spacings along the bottom plate and the top plate, wherein respective ones of said elongate pieces of lumber are operative for use in the bottom plate and/or the top plate, said respective elongate pieces of lumber having first and second ends and lengths therebetween, front surfaces and back surfaces, opposing sides extending between the front and back surfaces along the lengths thereof, and thickness dimensions between the front surfaces and the back surfaces, and between opposing sides thereof;
- (b) a plurality of stud locator markings spaced along the lengths of said elongate pieces of lumber at one or more surfaces which assist in defining respective ones of the thickness dimensions of said elongate pieces of lumber, each said stud locator marking defining a position for placement, on the respective said elongate piece of lumber, of an end of a stud dimension lumber piece having opposing front and back surfaces and a thickness dimension therebetween, to be joined to the respective said elongate piece of lumber, the respective said stud locator markings on the respective said elongate pieces of lumber indicating the positions where the front and back surfaces of respective stud lumber pieces are to intersect the respective said elongate piece of lumber; and

SN: 09/535,457

29462

- (c) at least one strap securing said plurality of elongate pieces of lumber together as said bundle,

the stud locator markings being spaced from each other along the lengths of said elongate pieces of lumber at at least one of the limited number of pre-determined stud spacings.